SIDLEY & AUSTIN

A PARTNERSHIP INCLUDING PROFESSIONAL CORPORATIONS

717 N. HARWOOD
DALLAS, TEXAS 75201
TELEPHONE 214 981 3300
FACSIMILE 214 981 3400

FOUNDED 1866

CHICAGO
LOS ANGELES
NEW YORK
WASHINGTON, D.C.

HONG KONG
LONDON
SHANGHAI
SINGAPORE
TOKYO

WRITER'S DIRECT NUMBER
214-981-3387

October 20, 1999

"Express Mail" mailing label number EL072274891US

Date of Deposit October 20, 1999

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Derrick Gordon
(Typed or printed name of person mailing paper or fee)

Derrick Gordon
(Signature of person mailing paper or fee)

October 20, 1999
Date of Signature

Assistant Commissioner
for Patents
Box Patent Application
Washington, D.C. 20231

Re: U.S. Patent Application
OPTICAL APPARATUS AND VIEWING OPTICAL SYSTEM THEREOF WHICH IS CAPABLE OF DISPLAYING INFORMATION
By: Ichiro KASAI
Our File: 15162/00910

Dear Sir:

Enclosed for filing are the following papers relating to an OPTICAL APPARATUS AND VIEWING OPTICAL SYSTEM THEREOF WHICH IS CAPABLE OF DISPLAYING INFORMATION, Ichiro KASAI, inventor:

(1) Specification;

(2) Unexecuted Declaration and Power of Attorney;

(3) Formal Drawings (8 sheets); and

(4) Check in the amount of $760.00 to cover the filing fee of the application.

In the event the attached check in the amount of $760.00 is not received with this correspondence, is not sufficient, or in the event additional fees are due, please charge the required fees (other than issue fee) during the pendency of this application to Deposit Account No. 18-1260. Please credit any overpayment to Deposit Account No. 18-1260.

All correspondence is to be directed to the Applicant's representative at the Dallas address listed above.

Respectfully submitted,



Daren C. Davis
Registration No. 38,425
Agent for Applicant

DCD/fis
Enclosures

"Express Mail" mailing label number EL072274891US

Date of Deposit October 20, 1999

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Derrick Gordon
(Typed or printed name of person mailing paper or fee)



(Signature of person mailing paper or fee)

October 20, 1999
Date of Signature

OPTICAL APPARATUS AND VIEWING OPTICAL SYSTEM THEREOF WHICH IS CAPABLE OF DISPLAYING INFORMATION

This application is based on Application No. H10-297991 filed in Japan, the content of which is hereby incorporated by reference.

FIELD OF THE INVENTION

The present invention relates to an optical apparatus having a viewing optical system. In one aspect, the present invention relates to a viewing optical system, suitable for use as a viewfinder optical system in, for example, single lens reflex cameras, lens shutter cameras, and digital still cameras, wherein the viewfinder optical system has an information display function.

BACKGROUND OF THE INVENTION

Viewing optical systems provided with holograms are well known. A hologram may be used as a condenser lens to match the pupil of the eyepiece with the objective

system (Japanese Laid-Open Patent Application No. SHO 51-19530), and also may be used as an information display. For example, the viewing optical systems disclosed in Japanese Laid-Open Patent Application Nos. SHO 58-27504 and SHO 59-185319 are provided with a hologram of a pre-recorded specific display pattern, and this pre-recorded display pattern is regenerated and displayed together with a photographic subject image.

In these viewing optical systems, only the specific display pattern recorded when the hologram was generated can be displayed and optional information not recorded in the hologram cannot be displayed.

SUMMARY OF THE INVENTION

An object of the present invention is to provide an improved viewing optical system.

Another object of the present invention is to provide a viewing optical system capable of displaying optional information using a hologram.

These objects are attained by providing a viewing optical system according to the embodiments described below.

A viewing optical system according to a first embodiment of the present invention has an objective system for forming an image of an object and an eyepiece system for enlarging and directing the image to the pupil. A viewing optical system is further provided with a hologram combiner comprising holograms of the volume type, phase type, and reflective type and having optical power for constructing a surface which is optically equivalent to the image surface at a different position than the image when viewed from the pupil. The viewing

optical system also includes an information display means for displaying information at the position of the equivalent surface, wherein the hologram combiner transmits light from the image and reflects light from the information display means so as to allow viewing of an image together with the information display overlaid onto the image.

In a viewing optical system according to a second embodiment of the present invention, the hologram combiner is arranged on the object side of the eyepiece system in the construction of the first embodiment.

A viewing optical system of a third embodiment provides, in the construction of the second embodiment, a Keplerian type viewing optical system in which the image is a real image, and wherein an inverting system is included to invert the image so that the object is viewed as an erect positive image. The hologram combiner is arranged within the inverting system.

A viewing optical system of a fourth embodiment provides, in the construction of the second embodiment, a hologram combiner which is a phase type hologram generated by dual light flux interference recordings, and wherein one of the preparation light fluxes is generated by an optical system identical to the eyepiece system.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and features of this invention will become clear from the following description taken in conjunction with the preferred embodiments with reference to the accompanying drawings, in which:

FIG. 1 is an optical structural diagram of a first embodiment of the present invention;

FIG. 2 is an optical structural diagram of a second embodiment of the present invention;

FIG. 3 is an optical structural diagram of a third embodiment of the present invention;

FIG. 4 is an optical structural diagram of a fourth embodiment of the present invention;

FIG. 5 is an optical structural diagram of a fifth embodiment of the present invention;

FIG. 6(A) is a schematic diagram of a relationship between preparation light and a photosensitive material when a hologram is recorded;

FIG. 6(B) is a schematic diagram of a relationship between regenerated light and a hologram when the hologram is regenerated;

FIG. 7 is a graphical representation of the hologram wavelength selectivity relative to the dual light flux angular difference;

FIG. 8 is an optical structural diagram of an embodiment of a reverse Galileo type viewfinder optical system;

FIG. 9 is an optical structural diagram of an embodiment of a relay type viewfinder optical system;

FIG. 10 is a pictorial view of a single lens reflex camera; and

FIG. 11 is a front view of a compact camera.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments of the viewing optical system of the present invention are described hereinafter with reference to the accompanying drawings. Like and equivalent parts are designated by like reference numbers throughout the several drawings, and duplicate descriptions are omitted where appropriate.

FIG. 1 shows the optical structure of a first embodiment of the present invention. The first embodiment is a viewfinder optical system for a single lens reflex camera, such as that shown in FIG. 10, and is provided with an objective system (LO) for forming the image of an object as an image (I1), and an eyepiece system (LE) for enlarging and directing the image of the hologram (H) to the pupil (EP). This viewfinder optical system includes the construction of a typical viewfinder optical system including an objective system (LO), a mirror (M1), a focusing screen (P1), a condenser lens (LC), a penta-roof prism (PD), an eyepiece system (LE), and a protective glass (P2), and further comprises an illumination light source (LT), a display element (DD), and a hologram combiner (HC). In the drawing, reference FL refers to a film surface.

An object image (I1) is formed on the focusing screen (P1) by the objective system (LO), and the object light emitted from the focusing screen (P1) constructs the viewfinder screen. The object light from the image (I1) is condensed by the condenser lens (LC) and enters the pentagonal prism (PD). The pentagonal prism (PD) comprises an inverting system for inverting an image so as to allow an object to be viewed as an erect positive image. After the image is inverted by the pentagonal prism (PD), the object light emitted from the pentagonal prism (PD) is transmitted through the eyepiece system

(LE), the protective glass (P2), and arrives at the pupil (EP).

The pentagonal prism (PD) has a plurality of surfaces including an incidence surface (S1), a roof reflecting surface (first and second reflecting surfaces)(SD), a final reflecting surface (third reflecting surface)(SR), and an exit surface (S2), wherein the hologram combiner (HC) is arranged on the final reflecting surface (SR). That is, the surface on the front of the pentagonal prism (PD) is a transmission surface (ST), and the hologram combiner (HC) is positioned between the transmission surface (ST) and the final reflecting surface (SR). The hologram combiner (HC), which comprises volume type, phase type, and reflective type holograms, functions to transmit the object light from the image (I1) and reflect the information display light from the display surface (IM) of the display element (DD). The hologram formed by the hologram combiner (HC) is not the recording of a specific display image, but rather the hologram combiner (HC) functions as a combiner lens to overlay the information display onto the object light.

The display element (DD) and the illumination light source (LT) comprise the information display means. The display element (DD) is an optical modulation element such as a liquid crystal display (LCD), and modulates the light from the illumination light source (LT) so as to display optional information on the display surface (IM). The displayed information may include exposure related data (e.g., shutter speed, f-stop value, exposure correction value), photographic area (e.g., field frame display), distance measuring area (e.g., AF frame display), photometric area (e.g., photometric frame display), focus detection result (e.g., focused/unfocused

or front focus/back focus), focus adjustment direction, flash related data, and the like. A replaceable mask also may be used at the display surface (IM) position rather than an optical modulation element such as an LCD. Furthermore, a self-emitting type display device provided with a light-emitting diode (LED) or the like may be used as the information display means.

The hologram combiner (HC) has optical power for constructing a surface which is optically equivalent to the image (I1) at a different position than the image (I1) when viewed from the pupil (EP). The display surface (IM) of the display element (DD) is positioned at an optically equivalent surface to the image (I1) as viewed from the pupil (EP). That is, the display element (DD) is arranged such that the parallel light flux from the pupil (EP) is reflected by the hologram combiner (HC) and forms an image at the position of the display surface (IM). Accordingly, the object light from the image (I1) is transmitted through the hologram combiner (HC) before and after being reflected by the reflection surface (SR), and the information display light from the display surface (IM) is reflected by the hologram combiner (HC). The light transmitted (object light) by the hologram combiner (HC) and the reflected light (information display light) both continue to the eyepiece system (LE), and the image formed by the transmitted light and the information display image formed by the reflected light are projected as virtual images at the same position via the eyepiece system (LE). That is, the information display is overlaid onto the image (I1) so as to be viewed together with the photographic object within the viewfinder field.

A hologram having a high wavelength selectability must be used in the hologram combiner (HC). When the

wavelength selectability is low, the object light of wavelengths outside the wavelength of the information display are reflected by the hologram combiner (HC). For this reason a reflective type hologram is used in the hologram combiner (HC). A reflective type hologram has extremely high wavelength selectability compared to a transmission type hologram. That is, the reflective type hologram responds to specific wavelengths but does not respond to other wavelengths. Since a reflective type hologram does not respond to the wavelengths of the object light (i.e., wavelengths which are the same as those of the information display), the object light is virtually unaffected by the hologram combiner (HC). Accordingly, the image and the information display image are both bright and superbly viewable. This significant advantage is not obtainable by using a transmission type hologram.

Wavelength selectability is described in detail below. FIG. 6(A) shows the relationship between the preparation light (La,Lb) and the photosensitive material (H) when the hologram is recorded, and FIG. 6(B) shows the relationship between the regenerated light (La',Lb') and the hologram (H') when the hologram is regenerated. La represents the object light (wavelength λ_0), Lb represents the reference light (wavelength λ_0), La' represents the regenerated object light, and Lb' represents the regenerated reference light (wavelength λ_c). Consider the hologram (H') when the object light (La) enters perpendicularly to the photosensitive material (H).

The regenerated light intensity, when the regenerated light wavelength (λ_c) shifts from the recorded wavelength (λ_0), exhibits a behavior similar to that of angular selectivity. The spread of the intensity ($\Delta\lambda$)

from the maximum wavelength (λ_0) to the wavelength initially at 0, and the angular change ($\Delta\theta$) in conjunction therewith, can be approximately expressed by equations (1) and (2) below:

$$\Delta\lambda = \frac{dz \cdot \lambda 0}{T} = \frac{\lambda_0^2}{T(n \pm \sqrt{n^2 - \sin^2\theta r})} \qquad (1)$$

$$\Delta\theta = \sin \theta r \times \frac{\Delta\lambda}{\lambda 0} \qquad (2)$$

wherein:

θr represents the incidence angle of the reference light (Lb);

n represents the refractive index of the photosensitive material (H);

λ_0 represents the recorded wavelength;

dz represents the distance of the interference fringes in the thickness direction of the photosensitive material; and

T represents the thickness of the photosensitive material (H).

The wavelength selectivity improves as the $\Delta\lambda$ becomes smaller. Accordingly, considering equations (1) and (2), the wavelength selectivity improves as:

(a) the photosensitive material (hologram) is thicker (T is greater);

(b) dz is smaller (θr is larger);

(c) refractive index (n) of the photosensitive material is larger; and

(d) the recorded wavelength (λ_0) is shorter.

FIG. 7 shows the wavelength selectivity (wavelength spread $\Delta\lambda$) of a reflective type hologram (HR) and a transmission type hologram (HT) relative to the angular difference (θr) of two light fluxes when the photosensitive material has a refractive index n=1.5, the generated wavelength λ_0=500 nm, and the photosensitive material thickness T=5 μm. It can be understood that when the angular difference θr between two light fluxes exceeds 90° (in the case of the reflective type hologram (HR)), the wavelength selectivity is rather higher than that of a transmission type hologram (HT).

Although light corresponding to high order diffracted light is regenerated by a plane type hologram (i.e., a so-called thin type hologram), only single order light is regenerated by a volume type hologram (i.e., the so-called thick type hologram). Accordingly, a volume type hologram capable of producing high diffraction efficiency is desirable as a hologram combiner (HC). In an amplitude type hologram, the regenerated illumination light is absorbed as it passes through the hologram, but light is not absorbed by a phase type hologram. Accordingly, a phase type hologram capable of producing a bright information display image is desirable as a hologram combiner (HC). Since the reflective type hologram has a greater angular selectivity than a transmission type hologram, in the case of a volume type hologram, the use of a volume type/reflective type hologram is advantageous in that it provides greater freedom in arrangement of the hologram combiner (HC). For the above-stated reasons, a volume type/phase type/reflective type hologram is used as the hologram combiner (HC) in the present embodiment.

As previously stated, the hologram combiner (HC) has optical power for constructing a surface which is

optically equivalent to the image (I1) but at a different position than the image (I1) when viewed from the pupil (EP). This optical power includes optical power to deflect the information display light from the display surface (IM) to the eyepiece system (LE), and optical power, such as that of a positive lens, to move the position of the display surface (IM) to the pentagonal prism (PD). The surface which is optically equivalent to the image (I1) is arranged nearer to the image (I1) via the optical power to deflect the information display light and is arranged at the endface position of the pentagonal prism (PD) via the positive lens-like power. As previously mentioned, optional display patterns are displayable via the arrangement of the display surface (IM) of the display element (DD) at the equivalent surface.

The information display image and the image can be at different enlargement ratios (i.e., focal lengths) relative to an observer via the lens-like optical power of the hologram combiner (HC). In this way the size of the information display image, and the size of the display surface (IM) can be reduced. Furthermore, the position of the display surface (IM) can be arranged at a suitable surface of the pentagonal prism (PD) since the display element (DD) can be freely arranged. When the hologram combiner (HC) does not possess a lens-like optical power, a large size display element (DD) of the display surface (IM) must be arranged at a position separated from the pentagonal prism (PD), thereby enlarging the overall scale of the viewfinder optical system. As previously mentioned, providing the hologram combiner (HC) with a lens-like optical power produces a wide display area and a compact structure.

In regard to the arrangement of the hologram combiner (HC), it is desirable that the hologram combiner (HC) is arranged on the object side (i.e., the front) of the eyepiece system (LE) as in the present embodiment. When the hologram combiner (HC) is arranged on the object side of the eyepiece system (LE), the information display image and the image (image (I1)) are aligned and enlarged for viewing via the eyepiece system (LE), thereby reducing the total focal length of the information display system. Accordingly, the display surface (IM) can be smaller, so as to provide a more compact viewfinder optical system. Furthermore, since the lens-like optical power required by the hologram combiner (HC) can be reduced, there is an advantageous reduction of degradation due to aberration in the information display system. As a result, an excellent, high-resolution information display image is obtained.

The hologram combiner (HC) is a phase type hologram generated by a dual flux interference recording, and one of the preparation lights (object light or reference light) is desirably produced by an optical system identical to the eyepiece system (LE). The hologram combiner (HC) produces the highest diffraction efficiency when prepared by a light flux identical to that during actual use of the hologram, so as to produce an information display image which is bright around the edges. The use of such light flux is a condition for producing the best aberration correction by the hologram. Accordingly, the use of a hologram combiner (HC) of the aforesaid construction provides a bright and highly detailed information display.

In viewfinder optical systems of the Keplerian type (real image type) wherein the image (I1) is a real image as in the present embodiment, an inverting system must be

used to invert the image so as to view the object image as an erect positive image. The pentagonal prism (PD) forms this inverting system. The hologram combiner (HC) is arranged within the pentagonal prism (PD). Placement of the hologram combiner (HC) within the inverting system is desirable from the perspective of providing a compact and highly efficient hologram combiner (HC).

When the inverting system is formed by the block of the pentagonal prism (PD) having a plurality of endfaces, as in the present embodiment, and the hologram combiner (HC) is arranged on an endface of the block (i.e., the endface of the inverting system), it is unnecessary to provide a separate space for the hologram combiner (HC). In this way the structure is compact and highly efficient. When the hologram combiner (HC) is provided on the endface of the block, the information display light is inverted by the hologram combiner (HC) and joins the object light, such that the information display light must be reflected in an internal direction of the block. In this way the information display light from other endfaces of the block are directed toward the interior of the block. Since the inverting system includes a penta-roof structure in the present embodiment, the hologram combiner (HC) is arranged on the final reflective surface (SR) such that the information display light enters from a gap between the roof reflective surface (SD) and the exit surface (S2). This arrangement is efficient in the viewfinder optical system of the penta-roof type used in single lens reflex cameras.

FIG. 2 shows the optical structure of a second embodiment of the present invention. An aspect of the second embodiment is that the information display system is incorporated within the image re-forming system, and the second embodiment is in other aspects identical to

the first embodiment. The image re-forming system is arranged between the display surface (IM) and the hologram combiner (HC), and comprises a mirror (M2), an image forming lens (L1), and an incidence surface (S1') forming a lens surface.

From the perspective of the brightness of the information display, it is desirable that the entrance of the information display light to the pentagonal prism (PD) is accomplished from an optical surface not used in the optical path of the object light (i.e., an optical surface at a gap in the optical path of the object light). For this reason the entering flux of the information display light must be reduced as much as possible. In the present embodiment, the display element (DD) is arranged such that the image forming surface (I2) re-forms an image at the display surface (IM) position via the image re-forming system, and an approximately conjugate correspondence is set between the incidence surface (S1') and the pupil (EP) from the image re-forming system so as to match the pupil of the information display light at the incidence surface (S1') via the hologram combiner (HC). Since the pupil of the information display light matches the incidence surface (S1'), the incidence flux of the information display light is reduced at the incidence surface (S1') position. Since the image forming magnification of the image re-forming system can be freely set, enlargement of the display area can be achieved, so as to provide a wider display area than with the first embodiment. Since the display element (DD) is also reduced in size, a compact viewfinder construction can be realized.

FIG. 3 shows the optical structure of a third embodiment of the present invention. An aspect of the third embodiment is that the image re-forming system

comprises a pancake type image forming lens (L2) which is incorporated into the information display system. In other aspects, the third embodiment is identical to the second embodiment, and the effectiveness of the image re-forming lens is similar to that of the second embodiment. The image forming lens (L2) has a selective reflective surface (SP) on the pentagonal prism (PD) side and uses a cholesteric liquid crystal panel and/or the like for the selective reflective surface (SP). The image forming lens (L2) has a concave reflective surface so as to improve the aberration performance of the information display light and allow high resolution viewing as compared to the first embodiment.

FIG. 4 shows the optical structure of a fourth embodiment of the present invention. Aspects of the fourth embodiment are that the hologram combiner (HC) is arranged on the object light incidence surface (S1) of the pentagonal prism (PD), and the image-reforming system, comprising an image forming prism (L3), is incorporated into the information display system. In other aspects the fourth embodiment is similar to the first embodiment and achieves an effectiveness similar to the second embodiment.

In this embodiment, the display element (DD) is arranged so as to re-form the image forming surface (I2) at the display surface (IM) via the image forming prism (L3), and an approximately conjugate correspondence is set between the incidence surface (S1') and the pupil (EP) by the image forming prism (L3) so as to match the pupil of the information display light at the incidence surface (S1') via the hologram combiner (HC). Since the inverting system is incorporated in the penta-roof structure, the hologram combiner (HC) is arranged on the incidence surface (S1) of the object light, and the

information display light enters through a gap between the roof reflective surface (SD) and the final reflective surface (SR). This arrangement is efficient in the viewfinder optical system of the penta-roof type used in single lens reflex cameras.

FIG. 5 shows the optical structure of a fifth embodiment of the present invention. The fifth embodiment is provided with an objective system (LO) for forming an image (I1) and an eyepiece system (LE) for enlarging and directing the image (I1) to the pupil (EP). This embodiment is a viewfinder optical system of the separate real image type for lens shutter cameras, such as that shown in FIG. 11. This viewfinder optical system includes the construction of a typical viewfinder optical system of an objective system (LO), field frame (MS), first prism (Pr1), second prism (Pr2), eyepiece system (LE), and further comprises an information display system having an illumination light source (LT), display element (DD), and hologram combiner (HC).

The inverting system of the present embodiment comprises a first prism (Pr1) having a roof reflective surface (SD), and a second prism (Pr2) arranged with a small space between the first prism (Pr1). The gap between the first prism (Pr1) and the second prism (Pr2) forms the TIR surface (SS) of total reflection and transmission, and directs the object light to the pupil (EP). A hologram combiner (HC) is provided on the second prism (Pr2) side of the TIR surface (SS), such that the object light passes through the hologram combiner (HC), and the information display light from the display surface (IM) is reflected by the hologram combiner (HC). The light transmitted by the hologram combiner (HC) (i.e., the object light) and the light reflected by the hologram combiner (HC) (i.e., the information display

light) are both directed toward the eyepiece system (LE), such that the image formed by the transmitted light and the information display image formed by the reflected light are projected as virtual images at the same position by the eyepiece system (LE). That is, the information display is overlaid on the image (I1) and viewed together with the photographic image in the field of the viewfinder.

In the case of a real image type viewfinder, a target mark such as an AF frame is arranged at the position of the image (I1), but to achieve this arrangement, a physical surface is required at the position of the image (I1). If foreign matter, such as dust, dirt, etc., adheres to this physical surface, the foreign matter is also enlarged together with the image (I1) by the eyepiece system (LE) and the overlaid matter is visible in the field of view, thereby reducing quality. In the viewfinder optical system of the present embodiment, a physical surface is not required at the image (I1) since the information display of the target mark and the like is accomplished by the hologram combiner (HC). Accordingly, foreign matter is not visible in the clear field of view.

The constructions using the hologram combiner (HC) as in the previously described embodiments are not limited to real image type viewfinder optical systems, inasmuch as these constructions are applicable to virtual image type viewfinder optical systems, such as the reverse Galileo type system shown in FIG. 8, and are applicable to relay type viewfinder optical systems using a relay lens (LR) as an inverting system as shown in FIG. 9. In the relay type viewfinder construction shown in FIG. 9, a secondary image of the image (I1) and the information display image of the display surface (IM) are

overlaid at a position of the image forming surface (I2). The constructions using the hologram combiner (HC) are not limited to the viewfinder optical systems of cameras, inasmuch as these constructions are applicable to viewing optical systems of binoculars, microscopes and the like. Although the inverting systems are formed using prisms in the previously described first through fifth embodiments, it is to be noted that the inverting system may be constructed by combining surface reflecting members such as a hollow penta mirror. In this instance, if a hologram combiner (HC) is adhered to the surface of a plane mirror, a effectiveness is obtained similar to that of the previously described embodiments.

As described above, the present invention realizes a viewing optical system capable of displaying optional information using a hologram.

Although the present invention has been fully described by way of examples with reference to the accompanying drawings, it is to be noted that various changes and modification will be apparent to those skilled in the art. Therefore, unless otherwise such changes and modifications depart from the scope of the present invention, they should be construed as being included therein.

WHAT IS CLAIMED IS:

1. A viewing optical system comprising:

an objective system for forming an image of an object;

an eyepiece system for enlarging and directing the image to a pupil;

a hologram combiner comprising a volume-type, phase-type, and reflective-type hologram and having an optical power for constructing an equivalent surface which is optically equivalent to the image surface at a different position than the image surface as viewed from the pupil; and

an information display means for displaying information on the equivalent surface,

wherein the hologram combiner transmits light from the image and reflects light from the information display means so that the image can be viewed with the information overlaid thereon.

2. A viewing optical system, as claimed in claim 1, further comprising:

a mirror for reflecting the image formed by the objective system;

a focusing screen;

a condenser lens; and

a pentagonal prism for inverting the image, said pentagonal prism having a plurality of surfaces, said hologram combiner being disposed on one of said plurality of surfaces.

3. A viewing optical system, as claimed in claim 2, wherein said information display means comprises an illumination light source and a display element, said display element for modulating light from the illumination light source so as to display information on the equivalent surface.

4. A viewing optical system, as claimed in claim 2, said information display means comprising:

an illumination light source;

a display element, said display element for modulating light from the illumination light source so as to display information on the equivalent surface;

an image reforming mirror;

an image forming lens; and

an incidence surface,

wherein said display element modulates light from the illumination light source so as to display information, said image reforming mirror reflects the information, displayed by the display surface, toward the image forming lens, and said image forming lens transmits the information to the equivalent surface.

5. A viewing optical system, as claimed in claim 2, said information display means comprising:

an illumination light source;

a display element; and

an image forming lens having a selective reflective surface,

wherein said display element modulates light from the illumination light source so as to display information and said image forming lens transmits the information to the equivalent surface.

6. A viewing optical system, as claimed in claim 2, said information display means comprising:

an illumination light source;

a display element; and

an image forming prism,

wherein said display element modulates light from the illumination light source so as to display information and the image forming prism transmits the information to the equivalent surface.

7. A viewing optical system, as claimed in claim 1, further comprising:

a field frame; and

an inverting system comprising a first prism and a second prism arranged with a small space therebetween, the small space forming a TIR surface, the hologram combiner being disposed on a second prism side of the TIR surface, and

wherein the objective system comprises a plurality of lenses and a prism.

8. A viewing optical system, as claimed in claim 1, wherein the viewing optical system is a reverse Galileo type optical system.

9. A viewing optical system, as claimed in claim 1, further comprising a relay lens for inverting the image.

10. An optical apparatus comprising a viewing optical system, said viewing optical system comprising:

an objective system for forming an image of an object;

an eyepiece system for enlarging and directing the image to a pupil;

a hologram combiner comprising a volume-type, phase-type, and reflective-type hologram and having an optical power for constructing an equivalent surface which is optically equivalent to the image surface at a different position than the image surface as viewed from the pupil; and

an information display means for displaying information on the equivalent surface,

wherein the hologram combiner transmits light from the image and reflects light from the information display means so that the image can be viewed with the information overlaid thereon.

11. An optical apparatus, as claimed in claim 10, said viewing optical system further comprising:

a mirror for reflecting the image formed by the objective system;

a focusing screen;

a condenser lens; and

a pentagonal prism for inverting the image, said pentagonal prism having a plurality of surfaces, said hologram combiner being disposed on one of said plurality of surfaces.

12. An optical apparatus, as claimed in claim 11, wherein said information display means comprises an illumination light source and a display element, said display element for modulating light from the illumination light source so as to display information on the equivalent surface.

13. An optical apparatus, as claimed in claim 11, said information display means comprising:

an illumination light source;

a display element, said display element for modulating light from the illumination light source so as to display information on the equivalent surface;

an image reforming mirror;

an image forming lens; and

an incidence surface,

wherein said display element modulates light from the illumination light source so as to display information, said image reforming mirror reflects the information, displayed by the display surface, toward the image forming lens, and said image forming lens transmits the information to the equivalent surface.

14. An optical apparatus, as claimed in claim 11, said information display means comprising:

an illumination light source;

a display element; and

an image forming lens having a selective reflective surface,

wherein said display element modulates light from the illumination light source so as to display information and said image forming lens transmits the information to the equivalent surface.

15. An optical apparatus, as claimed in claim 11, said information display means comprising:

an illumination light source;

a display element; and

an image forming prism,

wherein said display element modulates light from the illumination light source so as to display

information and the image forming prism transmits the information to the equivalent surface.

16. An optical apparatus, as claimed in claim 10, said viewing optical system further comprising:

a field frame; and

an inverting system comprising a first prism and a second prism arranged with a small space therebetween, the small space forming a TIR surface, the hologram combiner being disposed on a second prism side of the TIR surface, and

wherein the objective system comprises a plurality of lenses and a prism.

17. An optical apparatus, as claimed in claim 10, wherein the viewing optical system is a reverse Galileo type optical system.

18. An optical apparatus, as claimed in claim 10, further comprising a relay lens for inverting the image.

ABSTRACT OF THE DISCLOSURE

A viewing optical system of an optical apparatus has an objective system for forming an image of an object and an eyepiece system for enlarging and directing the image to the pupil. The viewing optical system also has a hologram combiner comprising holograms of the volume type, phase type, and reflective type and having optical power for constructing a surface which is optically equivalent to the image surface at a different position than the image when viewed from the pupil. The system also includes an information display means for displaying information at the position of the equivalent surface, wherein the hologram combiner transmits light from the image and reflects light from the information display means so as to allow viewing of an image together with the information display overlaid onto the image.



FIG. 1



FIG. 2



FIG. 3



FIG. 4



FIG. 5

FIG. 6(A)



FIG. 6(B)





FIG. 7



FIG. 8



FIG. 9

FIG. 10





FIG. 11

Attorney Docket No. 15162/00910

DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or I and the other persons listed below are the original, first and joint inventors (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

OPTICAL APPARATUS AND VIEWING OPTICAL SYSTEM THEREOF WHICH IS CAPABLE OF DISPLAYING INFORMATION

the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Attorney Docket No. 15162/00910

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

PRIOR FOREIGN APPLICATION(S)			Priority Not Claimed
10-297991	JAPAN	20/October/1998	☐
(Number)	(Country)	(Day/Month/Year Filed)	

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)	(Filing Date)
(Application No.)	(Filing Date)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose

information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Appl. No.)	(Filing Date)	(Status: Patented, Pending, Abandoned)
(Appl. No.)	(Filing Date)	(Status: Patented, Pending, Abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

John J. Arnott, Reg. No. 39,095
Charles S. Cotropia, Reg. No. 27,189
Kathi A. Cover, Reg. No. 37,803
Daren C. Davis, Reg. No. 38,425
William R. Gustavson, Reg. No. 29,160
David L. Hitchcock, Reg. No. 30,067
Kelly J. Kubasta, Reg. No. 44,196

Attorney Docket No. 15162/00910

William D. McSpadden, Reg. No. 44,234
Gary A. Ray, Reg. No. 40,313
Steven P. Rhines, Reg. No. 38,595
Thomas N. Tarnay, Reg. No. 41,341
James W. Williams, Reg. No. 20,047

Send correspondence to:
SIDLEY & AUSTIN
717 North Harwood
Suite 3400
Dallas, Texas 75201-6507

Direct telephone calls to:
Daren C. Davis
Direct: (214) 981-3335
Main: (214) 981-3300
Attorney Docket No.:
15162/00910

Full name of sole or first inventor

Ichiro		KASAI
First	Middle	Last

Inventor's signature: _____

Date: _____

Residence: Osaka-Shi (city) Osaka (prefecture) JAPAN (country)

Citizenship: Japan

Post Office Address: c/o Minolta Co., Ltd.
Osaka Kokusai Building, 3-31, 2-Chome, Azuchi-Machi,
Chuo-Ku, Osaka-Shi, Osaka 541-8556 JAPAN